

PRODUCT DATA SHEET



SFS INTEC PINK STRIP CLASS A+

Version No.2

Revision Date: 09/04/2021

Page 1 of 2

DESCRIPTION

SFS Intec Pink Strip Class A+ is a high performance butyl tape.

KEY FEATURES

Excellent adhesion to a wide range of substrates.

Good UV resistance

Highly conformable

Easy and accurate to use with little waste and no mess.

Remains flexible throughout its service life.

Unrivalled performance across a wide range of roofing applications. Exceeds the requirements of Class A in NFRC Technical Bulletin 36 'Performance Standards for Butyl Strip Sealants in Metal Clad Buildings'.

TECHNICAL APPROVALS

National Federation of Roofing Contractors (NFRC) Class A Performance – *Third party certification by a UKAS accredited laboratory.*

USES

High performance side & end lap joint, weather and air sealing in profiled roofing systems. Joining vapour control layer membranes. For use where a higher performance butyl tape is required that offers excellent bonding characteristics.

PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
DynamicTensile Adhesion	N/cm ²	25	H5
Dynamic Shear Adhesion	N/cm ²	20	H15
90 ° Peel Adhesion	N/cm	12	H48
180 ° Peel Adhesion	N/cm	24	H41
Specific Gravity	g/cm ³	1.5	H6
Moisture Vapour Transmission Rate	g/m ² /24hr/mm	0.13	ISO9932 / BS ISO 15106
Service Temperature Range	°C	-40 to +90	

H – HS Butyl Test Method

Gordleton Industrial Park,
Hannah Way, Sway Road,
Lymington, Hampshire,
SO41 8JD. UK.



T: +44 (0)1590 684400
F: +44 (0)1590 683728
E: sales@hsbutyl.com
W: www.hsbutyl.com

PRODUCT DATA SHEET



SFS INTEC PINK STRIP CLASS A+

Version No.2

Revision Date: 09/04/2021

Page 2 of 2

APPLICATION

PROPERTIES

Application temperature range: +5°C to +40°C

Shelf life: 24 months when stored flat in original packaging in cool, dry conditions.

INSTRUCTIONS

Surface preparation: All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, HS Butyl recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the butyl tape.

Application: Apply direct from the reel onto one surface and press sufficiently along its whole length to achieve good initial adhesion. Remove backing paper and offer other surface to the tape and push firmly to seal across the joint.

PACKAGING

The product is normally supplied as an extruded strip on a siliconised release paper. A wide range of dimensions can be supplied. Product dimensions will determine the number of rolls per carton.

Available colours: Pink.

TOLERANCES

Rectangular sections:

Thickness $\pm 10\%$

Width: up to 25mm ± 1 mm

26mm to 100mm ± 2 mm

over 100mm ± 3 mm

Bead sections:

Thickness $\pm 10\%$

Width $\pm 10\%$

GENERAL

SFS Intec Pink Strip Class A+ is part of a range of butyl products for Construction & Roofing markets. For further information, please contact our Customer Care Team or visit our Website.

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E & OE.

Gordleton Industrial Park,
Hannah Way, Sway Road,
Lymington, Hampshire,
SO41 8JD. UK.



T: +44 (0)1590 684400
F: +44 (0)1590 683728
E: sales@hsbutyl.com
W: www.hsbutyl.com